

**CUSTOMER PREMISES EQUIPMENT THAT CAN SUPPORT MULTIPLE CALL
CONTROL LANGUAGES OR MULTIPLE CALL AGENTS**

FIELD OF THE INVENTION:

5 This invention relates to voice over Internet (VoIP) equipment, and more particularly to customer premises equipment (CPE) associated with the VoIP equipment.

BACKGROUND OF THE INVENTION:

Consumer premises equipment (CPE), used in Voice over Internet (VoIP) systems, often includes a variety of devices such as communications gateways (CG) or cable
10 modems. The CPE imparts the connectivity of the VoIP system to subscriber telephone equipment, computers, cable television, or other such devices. Each CPE is typically configured with one or more telephony endpoint to which a single subscriber telephone connects. A call agent is connected to the Internet (IP) network, and the call agent acts to set up and break down the telephone communications over the VoIP system. A single
15 CPE communicates with a single call agent using a single call control language to provide VoIP services to the single CPE. Each call agent is typically operated, controlled, and granted access by a distinct service provider such a long-distance carrier or a local carrier. Different service providers may provide their VoIP services using a slightly different call control language. Requiring a single control language be used by a CPE limits the
20 potential variety of VoIP services that can be selected by the VoIP customers. If the user wants to be able to select one of multiple call agents, call control languages, or service providers, then it may be necessary for the user to undergo the expense of connecting multiple telephone lines to their business or home.

It would be desirable to configure the CPE equipment to have the ability to interact with multiple service providers, with each one of the multiple service providers possibly using a distinct call agent and a distinct call control language. For CPE users, it may also be desired to use their CPE so each subscriber telephone can provide a selection of multiple services, call agents, or call control languages.

SUMMARY OF THE INVENTION:

The present invention is directed to an apparatus and associated method a consumer premises equipment (CPE) configured to be connected with one of a selectable plurality of call agents using one of a selectable plurality of call control languages in response to user input to the telephone. In one aspect, telephone users can therefore select, e.g., a service provider. In another aspect, the CPE provides VoIP service to a telephone.

BRIEF DESCRIPTION OF THE DRAWINGS:

The accompanying drawings, which are incorporated herein and constitute part of this specification illustrate a preferred embodiment of the invention.

Fig. 1 is a block diagram of one embodiment of a Voice over Internet (VoIP) system;

Fig. 2 shows one embodiment of call control signal diagram displaying call control signals associated with the VoIP system of FIG. 1;

Fig. 3 is a block diagram of one embodiment of consumer premises equipment (CPE) shown in the VoIP system shown in FIG. 1;

Fig. 4 shows a flow chart of embodiment of method performed by the consumer premises equipment (CPE) of FIG. 3 in selecting one call agent or call control language in which to make a call over the VoIP system shown in FIG. 1; and

Fig. 5 shows one embodiment of VoIP connection between multiple subscriber telephones (connected to a single customer premises equipment (CPE)) and multiple call agents.

DETAILED DESCRIPTION OF THE EMBODIMENT:

5 This disclosure describes an embodiment, shown in FIG. 1, of a Voice over Internet (VoIP) system 100 that is used to provide telephone service between subscriber telephones 107. The user can select the type of service (service provider, call agent, or call control language) desired. The general structure and operation of the VoIP system 100 is described. A method by which a user selects one of a plurality of telephone services is also described.

FIG. 1

20

The VoIP system 100 provides for voice communication between a plurality of customer premises equipment (CPE) 101 using a combination of an Internet (IP) network 106 and a hyper fiber coax network (HFC) 102. Alternatively, the VoIP system 100 provides for voice communication between a CPE 101 and a CPE 118 over the IP network 106, the HFC 102, and a LEC circuit switched network 116. The CPE 101 is configured to include, e.g., a cable modem 103 and a subscriber telephone 107, or any other communication device such as a communications gateway (CG) 104 or broadband telephony interface (BTI) that allows for subscriber telephone 107 to communicate over the IP network 106. A HFC 102 is configured to provide optic-based cable communications between the CPE 101 and a cable modem termination system (CMTS) 105.

The embodiment of VoIP system 100 shown in FIG. 1 includes the CPE 101 (that includes the cable modem 103, the HFC 102, the CMTS 105, the IP network 106, one or more subscriber telephones 107, a plurality of call agents 108 and 109, a trunking gateway 110, a signaling gateway 112, a local exchange carrier (LEC) signaling packet network

039362.0065

114, a LEC circuit switched network 116, a remote CPE 118, and a plurality of subscriber telephones 107 coupled to the CPE 118. The VoIP system 100 provides communication using the IP network 106 between the subscriber telephones 107 connected respectively to the CPE 101 and/or the remote CPE 118.

5 Also included in the VoIP system 100 is a first service provider 160, a second service provider 162, a provision server 164, and a signaling server 166. The service providers 160, 162 may be configured as servers, standalone computers, or any computer that provides access to the VoIP service to the subscriber telephones 107. The signaling server 166 may be configured as a server, a standalone computer, or any computer that provides signaling capabilities to the VoIP system. The provision server 164 may be configured as a server, a standalone computer, or any computer that provides provision options to users of subscriber telephones 107. Though the service providers 160, 162, the signaling server 166, and the provision server 164 are shown in communication with the IP network 106 in the embodiment of FIG. 1, it is envisioned that one or more of these servers may be physically resident on the LEC circuit switched network 116, on the LEC signaling packet network 114, or on the HFC 102 where appropriate. The VoIP system 100 provides communication using the IP network 106 between telephone handsets 107 connected to the CPE 101 and/or the remote CPE 118.

20 The HFC 102 allows for the cable modem 103 to communicate via the CMTS 105 over the IP network 106. This disclosure describes the interaction between one embodiment of CPE 108, as shown in FIG. 2, and other portions of the VoIP system 100. The HFC 102 allows for data and IP voice to share the bandwidth with television channels. The CPE 101 includes one or a plurality of telephone end points to which the subscriber

039362.0065

telephone 107 connects. The CMTS 105 can be configured to provide for data, cable TV and/or telephone applications.

One embodiment of HFC 102 uses the Data Over Cable Systems Interface Specification (DOCSIS) protocol. DOCSIS is a standard for the cable modem interface
5 over the HFC 102 between a cable TV operator and a computer or subscriber telephone. DOCSIS has been accepted as a standard since DOCSIS 1.0 when it was ratified by the International Telecommunication Union (ITU) in March of 1998. Cable modems conforming to DOCSIS are commercially available from a variety of vendors.

Different embodiments of telephone service use the VoIP system 100. One
10 embodiment of VoIP service is referred to as "on-net calls," in which multiple CPEs 101 communicate using the IP network 106 and/or the HFC 102 only. Another embodiment of VoIP telephone service is referred to as "off-net calls" in which a CPE 101 communicates with the remote CPE 118 over a hybrid network system including the LEC circuit switched network 116 portion and the IP network 106. Off-net calls involve not only the IP network
15 106 and the HFC 102 as do on-net calls, but also involve a LEC circuit switched network 116, a trunking gateway 110, and the signaling gateway 112 as shown in FIG. 1.

The selected call agent 108 or 109 initiates and terminates the calls in the IP network 106. Typically multiple call agents 108, 109 are connected to the IP network 106, and a different service provider may operate each call agent 108, 109. Each call agent 108
20 and 109 may use one of a variety of call control languages such as Network Control System (NCS), Simple Gateway Control Protocol (SGCP), Multimedia Gateway Control Protocol (MGCP), GR303, and others. The call agents 108 or 109 acts as a master of set-up and teardown for VoIP voice communications.

039362.0065

The call agents 108, 109 include the necessary hardware and software to provide the signals that initiate, monitor, regulate, and terminate VoIP communication. Each call agent 108, 109 maintains the call state, performs phone number to IP address translations, and implements class features. One embodiment of call agent 108, 109 is fashioned as a
5 server that runs an operating system such as a UNIX or WINDOWS NT[®] (A registered trademark of Microsoft Corporation of Redmond, WA). The call agents 108, 109 may be configured as a server, a stand-alone computer, a PC, or any type of computer having adequate processing, memory and I/O capabilities to provide VoIP service. The details of the call agents 108, 109 are depicted in FIG. 1.

10 The call agents 108, 109 includes a programmable central processing unit (CPU) 191 that is operable with a memory 192 (e.g., RAM, ROM, hard disk and/or removable storage) and well-known support circuits 193 such as power supplies, clocks, cache, and the like. Additionally, each call agent 108, 109 includes I/O circuits 197 that produce control signals, such as a control output signal, and receive signals such as an input signal.
15 By executing software stored in the memory 192, the call agents 108, 109 produces the output that leads to call set-up, call termination, voice transmission, and other features that provide for telephone communication over the VoIP system.

Each call agent interacts with a media terminal adapters (MTA) 136 or 138 that are included in their respective CPE as shown in the embodiment of FIG. 2. The plurality of
20 MTAs 136, 138 are integrated in the cable modem 103. Each MTA 136, 138 acts under the control of, and is configured to interact with, its respective call agent 108, 109. Each MTA 136, 138 is controlled by the respective call agents 108, 109 to monitor for events occurring at the subscriber telephone 107, and report events (e.g., an off-hook condition). Each MTA 136, 138 sets up and tears down RTP streams as commanded. Each call agent

039362.0065

108, 109 operates independently under the control of an associated MSO to command its respective MTA 136, 138 to monitor VoIP events, establish signal tones, and set up or tear down real time protocol (RTP) voice streams.

If, however, an off-net call is being made, then the VoIP system 100 has to establish communications to a Local Exchange Carrier (LEC) network portion 150 as well as the combined IP network 106 and HFC 102. Central offices included in the LEC circuit switched network 116 are used to set-up and break down the calls in the LEC circuit switched network 116 portion of the VoIP system. The communications between the IP network 106 and the LEC circuit switched network 116 can be categorized to include signal and voice communication portions. The signal communications establish and break down the channels by which the voice communications are transmitted. In one embodiment of off-net calls, the signal and the voice packets follow different routes (e.g. over the retrunking gateway 110 and the signaling gateway 112) between the IP network and the LEC circuit switched network 116.

The trunking gateway 110 shown in FIG. 1, provides for voice communication interconnection those portions of the VoIP system 100 that use the IP network (and communicate using the RTP protocol) and those portions of the VoIP system that use the LEC circuit switched network 116 (and use the phase code modulation (PCM) protocol). The trunking gateway 110 converts voice packets between the RTP packets used in the IP network 106 and the phase code modulation (PCM) packets used in the LEC circuit switched network 116.

The trunking gateway 110 sets up, maintains, and tears down voice streams provided between the IP network and the LEC circuit switched network 116.

039362.0065

The trunking gateway 110 thus has to provide for a mapping between the portions of the network that use the RTP protocol from those portions of the network that use the PCM protocol. The trunking gateway 110 sets up and tears down RTP and PCM streams, as commanded by the call agent 108, 109. The trunking gateway 110 therefore acts as a slave to either the call agent 108, 109 in the IP network 106 or the central office (not shown) in the LEC circuit switched network. The trunking gateway 110 also monitors the RTP packets in RTP streams transmitted between the IP network 106 and the LEC circuit switched network 116.

The LEC signaling packet network 114 controls the signaling provided over the signaling gateway 112 between the IP network 106 and the LEC circuit switched network 116. The signals will be transmitted between the IP network and the LEC circuit switched network 116 will result in the set up and break down of off-net calls via the signaling gateway.

FIG. 3 shows one embodiment of CPE 101 as shown in FIG. 1. The CPE includes the cable modem portion 350, a telephony interface portion 352, a central processing unit (CPU) 353, a memory 354, a receiver 349, and a transmitter 351. The cable modem portion 350 is configured to provide IP network data communications to, e.g., via an Ethernet media access control (MAC) 355 and a high speed data port RJ45 (Ethernet) computer connector 356 to a computer or hub 357 or via one or more RJ11 connectors to one or more subscriber telephone 107.

The cable modem portion 350 also includes an HFC media access control (HFC MAC) 358 that provides a layer 2 interface between the HFC 102 and the combined memory 354 and CPU 353. The CPU 353 may be shared by both the cable modem portion 350 and the telephony interface portion 352. An Ethernet MAC 355 provides an interface

039362.0065

between a PC or hub 357 and the CPU 253/memory 354. The telephony interface portion 352 is configured to provide IP network voice communications to, e.g., one or more subscriber telephones 107. The CPU 353 controls and manages the processes occurring within the CPE 101 by data transfer and data storage between the components of the CPE.

5 In one embodiment, the cable modem portion 350 includes a chip that integrates many of the above components. For example, Broadcom Corporation of Irvine, CA produces one commercially available cable modem chip as the BCM3350 that combines the integrated 64/256-Quadrature Amplitude Modulation (QAM) receiver 349, a
10 Quadrature Phase Shift Keying (QPSK)/16-Quadrature Amplitude Modulation (QAM) transmitter 351, a complete DOCSIS HFC media access control (MAC) 358, a MIPS32 CPU 353, and a memory interface.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193

039362.0065

ringer 366 produces a ring in a prescribed subscriber telephone 107 when called from another subscriber telephone 107.

The DSP 360 performs such voice protocol processing as compression, decompression, dial tone generation, dual tone multi-frequency (DTMF) tone detection, echo cancellation, etc. The DSP generates phase code modulation (PCM) signals what are sent to the CODEC 362. The DSP 360 also processes received PCM signals originating from the subscriber telephone 107 via the CODEC 362, and transfers the processed signal to the cable modem portion 350. The DSP is commercially available from such companies as Motorola, Incorporated of Schaumburg, IL and Texas Instruments of Dallas, TX.

The digital interface between the DSP 360 and the CODEC 362 uses pulse code modulation (PCM). The CODEC 362 receives digital information from the DSP 360 in the form of a bit-stream where, in one embodiment, the amplitude of the incoming signal is related to the digital value (e.g., a digital 0 or 1) being sent. The CODEC 362 processes the PCM signals from the DSP 360, and generates an analog signal that is transmitted to the appropriate SLICs.

In signals originating at the subscriber telephone, the CODEC 362 samples the signal from the SLIC 364 and translates the discrete amplitude into a digital number that is sent to the DSP, thereby translating the audio signals received from the SLIC into phase code modulated (PCM) signals that can be transferred to the DSP. The CODEC 362 transmits data to, and receives data from, the DSP utilizing the CODEC pins. The frame sync signals determine the frame's start position and the channel data that will be transmitted.

One SLIC 364 acts to connect the CPE 101 with one subscriber telephone 107. The appropriate SLIC 364 translates the analog signals received from the CODEC 362 into

039362.0065

voice signals (voltage levels) that can be converted by the subscriber telephone into voices or audible noises. The SLIC 364 also transfers audio signals from the microphone of the subscriber telephone 107 to analog signals that are received, and processed by, the CODEC. The SLIC 364 provides an interface between the RJ11 telephone jack 368 and the CODEC 362. The SLIC 364 interfaces with the CPU by sending an interrupt to the CPU, when necessary. The SLIC uses the interrupt to inform the CPU of the occurrence of events at the subscriber telephone. The SLIC 364 also contains circuits for loop-back testing that is used to test the operation of the subscriber telephone 107. The functions of the SLIC 364 includes limit is configured to echoes produced as signals encounter conductor discontinuities by flowing through portions of the CPE 101.

The memory 354 may include RAM or ROM portions. More particularly, the memory 354 includes a dynamic RAM (DRAM) that is configured to perform a variety of operations. Certain ones of the operations stored in the memory 354 that may be accessed by the CPU include a call control protocol engine 355, a signaling application 372, a provision application 374, and the media terminal adapters (MTA) 136, 138 with which the respective call agents 109, 108 interact. The call control protocol engine 355, the signaling application 372, the provision application 374, and the MTAs 136, 138 provide their operation with the interaction between the CPE 353 and the memory 354. The signaling application 372 interacts with the signaling server 166 shown in FIG. 1 to provide the signaling functionality to the CPE 101. The provision application 374 interacts with the provision server 164 to provide the provision functionality to the CPE 101. The use of multiple MTAs 136, 138 in the memory 354 provide for interaction of the CPE to different call agents 109, 108 using multiple call control languages.

Signaling packets are dynamically constructed on the DRAM, then the packets are sent via the HFC MAC 358 to the HFC 102 and the call agent 107 or 108. The signal application 372 interacts with the signaling server 166 shown in FIG. 1 to provide the signals necessary to set up, break down, or maintain the voice communications using the VoIP system. The provision application interacts with the provision server shown in FIG. 1 to provide user interaction with the VoIP system so the user can select a particular MSO, call agent, call options, call control language, etc. The HFC MAC 358 supports baseline privacy encryption, decryption, and transmission convergence sub-layer support. The HFC MAC 358 includes all features necessary for DOCSIS 1.0 and 1.1 compliance.

FIG. 2 shows one embodiment of call control signal diagram 200 that is provided over the VoIP system 100 that relates to the signaling to establish a call between a subscriber telephone 107a located at a first CPE 101a and a subscriber telephone 107b located at a second CPE 101b. The embodiment of call control signal diagram 200 shown in FIG. 2 may be used by one call agent 108 along with the first CPE 101a (or portion of CPE 101) that interacts with that call agent. Both the first CPE 101a and the second CPE 101b are configured, in one embodiment, similar to the CPE 101 shown in FIGs. 1 and 3. A slightly modified call control signal diagram (perhaps defined by one of the above standardized call control languages) may be used by a modified embodiment of call agent 109 (the call control signal diagram and the associated software being modified) along with the second CPE 101b (or portion of a CPE) that communicates with the call agent 109. The call control signal diagram 200 starts with an off-hook signal 202 is transmitted from the subscriber telephone 107a to the first CPE 101a. The off-hook signal 202 is transmitted, e.g., when the handset of the subscriber telephone 107a is lifted. Following the first CPE 101a receiving the off-hook signal, the first CPE 101a transmits a notify

039362.0065

signal 204 to the first call agent 109. In response to the notify signal 104, the first CPE 101a transmits a notify request signal 206.

Following the notify request signal 206 received by the first CPE 101a in the call control signal diagram 200, the first CPE 101a transmits a dial tone on signal 208 to the subscriber telephone 107a. As the subscriber telephone 107a receives the dial tone on signal 208, a dial tone is established in the ear-piece of the subscriber telephone 107a. At this time, the user can dial digits in the subscriber telephone corresponding to the phone number. As the digits are entered in the subscriber telephone 107a, a digit signal 210 including the dialed phone number is transmitted from the subscriber telephone 107a to the first CPE 101a. As the digit signal is received by the first CPE 101a, a dial tone off signal 212 is transmitted from the first CPE 101a to the subscriber telephone 107a. The dial tone off signal 212 deactuates the dial tone in the subscriber telephone 107a.

Following the digit signal 210 being received by the first CPE 101a, a notify session signal 214 is transmitted from the first CPE 101a to the first call agent 109. When the first call agent 109 receives the notify session signal 214, a create session signal 216 is transmitted from the first call agent to the first CPE 101a. The notify session signal 214 and the associated create session signal 216 are provided to create a session in which the RTP transmits voice over the VoIP system 100. After the create session signal 216 is received by the first CPE 101a, an acknowledgment (ACK) signal 218 is transmitted from the first CPE 101a to the first call agent 109. Following the reception of the ACK signal 218 at the call agent 109, the call agent 109 transmits a create signal 220 to the second CPE 101b. Following the reception of the created signal 220 at the second CPE 101b, a ring signal 221 is transmitted from the CPE 101b to the subscriber telephone 107b that creates a

039362.0065

ring in the subscriber telephone 107b. The ring is created using the ringer 336 contained in the subscriber telephone 107b.

Following the reception of the create signal 220 at the second CPE 101b, a ring on signal 222 is transmitted from the terminating CG 118 to the subscriber telephone 107a.

- 5 The ring on signal 222 indicates to the subscriber telephone 107a that the second CPE 101b is ringing its associated subscriber telephone 107b. The transmission of the ring on signal 222 by the CPE 101b limits such further activity of the CPE 101b as dialing another number.

Following the transmission of the ring on signal 222, an ACK signal 224 is transmitted from the second CPE 101b to the call agent 109. Following the reception of the ACK signal 224, the call agent 109 transmits a notify request signal 226 to the first CPE 101a. As the first CPE receives the notify request signal 226, a ringback on signal 228 is transmitted from the first CPE 101a to the subscriber telephone 107. The receipt of the ringback on signal 228 interacts with the ringer 366 to produce the ringing in the ear-piece of the subscriber telephone 107a indicating that the called telephone is ringing as a result of the ring signal 221.

Following the receipt of the ringback on signal 228, an off hook signal 230 is transmitted from the subscriber telephone 107a to its associated second CPE 101b. As the second CPE 101b receives the off hook signal 230, a notify signal 232 is transmitted from the second CPE 101b to the call agent 109. The off hook signal 230 allows the second CPE 101b to transmit the notify signal 232. Following the reception of the notify signal 232, the first call agent 109 transmits a modify signal 234 from the first call agent 109 to the first CPE 101a. Following the reception of the modify signal 234 of the first CPE 101a, a ringback off signal 236 is transmitted from the first CPE 101a to the subscriber

039362.0065

telephone 107a and a distinct modify signal 240 is transmitted from the call agent 109 to the second CPE 101b. An answer signal 241 is transmitted from the subscriber telephone 107b to the CPE 101b indicating the subscriber telephone has responded (by, e.g., a user picking up the handset or an answering machine responding). Upon reception of the
5 ringback off signal 236 at the subscriber telephone 107a, the ringing stops in the ear-piece of the subscriber telephone 107 connected to the first CPE 101a.

Following the reception of the distinct modify signal 240 received at the second CPE 101b from the call agent 109, a ring off signal 242 is transmitted from the second CPE 101b to the subscriber telephone 107b. The ring off signal 242 indicates that the
10 ringing at the second CPE 101b has been stopped. Following the transmission of the ring off signal 242, a VoIP voice transmission pathway 244 is established between the first CPE 101a and the second CPE 101b. The voice transmission pathway 244 provides for voice transmission between the subscriber telephone 107a located respectively at the first CPE 101a and the subscriber telephone 107b located at the second CPE 101b. The first local
15 transmission pathway 244 is typically established using a different path from that described for the signals 202 to 242.

The embodiment of call control diagram 200 is exemplary and not limiting in scope. The multiple call agents 108, 109 may, or may not, have a variety of call control languages. Each call control language is represented by a slightly different embodiment of
20 call control diagrams to provide interaction to only those CPEs 101 (and the associated telephony equipment such as the CG 104, CM 103, and subscriber telephones 107) that are configured to interact with those call control languages.

FIG. 4 shows one embodiment of method performed by the VoIP system 100 shown in FIG. 1 whose operation largely results from the call control protocol application

039362.0065

355 in the CPE 101. The method 400 allows for a user to select between multiple call control languages or multiple call agents while using a single CPE 101. In step 402, the user picks up a handset of a subscriber telephone 107 and dials 0, as a default to select a menu. This default selection acts to connect the local VoIP telephony service provider as shown in step 404. The provision application 374 of the memory 354 in the CPE 101 is configured to allow the user to select one of a variety of service providers, call connection languages, call agents, etc.

In step 406, the provision application 374 is actuated to interact with the provision server by an operator prompting a user for a number to choose, each number corresponds to a certain type of service provider, as can be handled by multiple call agents using multiple call control languages. For example, the operator application associated with the provision application may prompt the user to input the users selection the keypad of the subscriber telephone 107. For example, the operator may prompt the user to press "1" to select one service provider, press 2 to select for another service provider, or press different numbers for different call agent/call control language combinations associated with perhaps another service providers. The method 400 continues to step 408 in which, based on the input by the user, the database application associated with the provision application is input the CPE provision application 374 shown in FIG. 3 to provide the prompts to the user of the subscriber telephone 107. The database application is located in the provision server.

In step 410 of method 400, the CPE provision application inputs the application menu to the signaling application 372. The method 400 continues to step 412 in which the CPE provision application provides the application menu to the user in audio or graphics form (if graphics capabilities exist on the subscriber telephone). (An example of such a

039362.0065

menu might be "good morning, dial 01 to have service provided by AT&T, dial 02 to connect to have service by MCI, etc."). The method 400 continues to step 416 in which the user dials a number corresponding to the menu to select a choice on the keypad of the subscriber telephone. Based upon the user selection, the CPE will communicate to one of the call agents 108, 109 using the call control language of that agent. The method 400 continues to step 418 in which the choice dialed by the user in step 416 is forwarded to the signaling application 372.

In step 420, the signaling application, in response to the selected choice as prompted by the provision application, selects a particular call agent 108 to handle the call and provide the service. The method 400 continues to step 422 in which the service is established to the CPE 101 as provided by the call agent 108. The call agent 108 will dictate the type of service that is to be provided, including the call control language, the allowed service option, etc. based on the users selection dialed in step 416. The provision application 374 can also interface in a similar matter with the signaling application 372 to the method 400 to determine selected call options. For example, a certain call can be made using call waiting, caller identification "ID", or other services that may be provided.

In the embodiment shown in FIG. 4, a single user interfacing with a single subscriber telephone 107 connected to a single CPE 101 can select one out of multiple call control languages, MSOs, call agents, etc.

It is envisioned that a similar method as shown in FIG. 4, can be provided to each of a plurality of subscriber telephones 107 that are configured to each fit within a plurality of RJII telephone jacks 107 as shown in the embodiment in FIG. 3. For example, there are 4 subscriber telephones 107 shown in the embodiment of FIG. 3 as being connected to the CPE 101. A first user that connects to one of the subscriber telephones 107 can connect to

039362.0065

a selected one of a plurality of MSO's, call agents, call control languages, or calling options, using the method 400. A second user can pick up another one of the subscriber telephones, by interfacing with the signaling application 372 and the provision application 374, and can select either of the same call options, call control languages, call agents, as
5 provided to the first subscriber telephone 107. Alternatively, the second user may be required to select a different group of users, as indicated by the interaction between the CPE 101 and the remote call agents 108.

In the embodiment of telephone communications across the VoIP system 100 shown in FIG. 5, the CPE 101 is arranged to each subscriber telephone 107a to 107d can be in communication with a different service provider 160 or 162, using a different call agent and a different call control language. In FIG. 5, the CPE 101 is functionally subdivided into a plurality of CPE 101a, 101b, 101c, and 101d that are in respective communication with subscriber telephones 107a, 107b, 107c, and 107d. Each one of the plurality of CPE 101a, 101b, 101c, and 101d functionally include respective telephony interface portions 352a, 352b, 352c, and 352d and respective cable modem portions 350a, 350b, 350c, and 350d. Each of the telephony interface portions 352a, 352b, 352c, and 352d contains similar components (some of them may be shared) to the embodiment of telephony interface portion 352 shown in FIG. 2. Each of the cable modem portions 350a, 350b, 350c, and 350d contains similar components (some of them may be shared) as the
20 embodiment of cable modem portions 350 shown in FIG. 2.

In the embodiment shown in FIG. 5, the provision server 164 is configured so cable modem 350a communicates with service provider 160 using the Multimedia Gateway Control Protocol (MGCP) call control language to provide telephone service for subscriber telephone 107a. The cable modem 350b communicates with service provider 162 using

039362.0065

the MGCP call control language to provide telephone service for subscriber telephone

107b. The cable modem 350c communicates with service provider 160 using the MGCP

call control language to provide telephone service for subscriber telephone 107c. The

cable modem 350d communicates with service provider 162 using the Simple Gateway

5 Control Protocol (SGCP) call control language to provide telephone service for subscriber telephone 107d.

The embodiment of VoIP system 100 shown in FIG. 5 functionally illustrates how a plurality of subscribe telephones 107 that are connected to a single CPE 101 can each communicate with different call agents (and/or different service providers) using different call control languages.

While the principles of the invention have been described above in connection with the specific apparatus and associated method, it is to be clearly understood that this description is made only by way of example and not as a limitation on the scope of the invention. Though the above concepts have been described relative to a VoIP system, it is envisioned that the concepts also apply to the plain old telephone systems (POTS), digital telephone systems, and cellular telephones.